

CDINS16



CDINS16 : Din Rail Mounting Socket & Switch

Connectwell DIN Rail mounted socket and switches offer a unique possibility of mounting an Industrial Socket and Switch on a standard DIN rail.

Sockets are available for various country standard plugs. These need to be wired and snapped inside the Din rail mounting frame as shown in the assembly diagram below. This assembly then easily snaps on to a standard DIN rail.

TECHNICAL DATA

Socket and Switch Housing Material	Polycarbonate
DIN-Rail Frame Material	ABS
Wire Clamp and Contact Material	Brass
Rated Minimum Wire Size	0.5 mm ²
Rated Maximum Wire Size	2.5 mm ²
Rated Voltage	250 V
Rated Current	13 A

DIMENSIONS

Height	60 mm
Length	82 mm
Width	53 mm

ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
CDINS16	Din Rail Mounting Socket & Switch	5

ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA701-1M	Din 35 Rail unslotted 1 meter	50
	CA701-2M	Din 35 Rail unslotted 2 meter	50
	CA701-2M-S	Din 35 Rail slotted 2 meter	50
	CA701-1M-S	Din 35 Rail slotted 1 meter	50
	CA701-15-1M	Din 35 Rail 15 deep unslotted 1 meter	50
	CA701-15-1M-S	Din 35 Rail 15 deep slotted 1 meter	50
	CA701-15-2M	Din 35 Rail 15 deep unslotted 2 meter	50
	CA701-15-2M-S	Din 35 Rail 15 deep slotted 2 meter	50
	CA102	End Clamp in Polyamide suitable for Din32 / Din35 / Din35-15 Rails	50
	CA202	End Clamp in Polyamide suitable for Din 35 / Din 35-15 Rails	25

APPROVALS



ASSEMBLY INSTRUCTIONS

