

EPCDL4U



connectwell
THE RIGHT CONNECTION

End Plate

End Plates are used to cover the live parts of the last Terminal Block

PRODUCT SPECIFICATION

Height	43 mm
Length	55 mm
Width (Thickness)	2.4 mm

ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
EPCDL4U	End Plate in Grey colour suitable for CDL4U / CDL4U(I.S) / CDL4U(E) Terminal Block	50

SUITABLE FOR

CDL4U(E)RC	4 sq.mm Terminal Blocks with inbuilt RC circuit.
CDL4U(O)	4 sq.mm Double Level Terminal Blocks with open type current bars to house electronic components.
CDL4UED2	4 sq.mm Terminal Blocks with diode circuit - D2 configuration
CDL4UED4	4 sq.mm Terminal Blocks with diode circuit - D4 configuration
CDL4UEDD2	4 sq.mm Terminal Blocks with diode circuit - DD2 configuration
CDL4UEL1	4 sq.mm Double Level Terminal Blocks with LED indication - L1 Configuration
CDL4UEMOV	4 sq.mm Surge Suppression Terminal Blocks with MOV
CDL4U	4 sq.mm Double Level Terminal Blocks.
CDL4UED3	4 sq.mm Terminal Blocks with diode circuit - D3 configuration
CDL4UEDD3	4 sq.mm Terminal Blocks with diode circuit - DD3 configuration
CDL4UELA	4 sq.mm Surge Suppression Terminal Blocks with Lightning Arrestor.
CDL4UEL3	CDL4U(E)LD3 : 4 sq.mm Double Level Terminal Blocks with LED indication - LD3 Configuration
CDL4UERR1	4 sq.mm Terminal Blocks with resistor circuit - RR1 configuration
CDL4U(I.S)	4 sq.mm Double Level Internally Shorted Terminal Blocks.
CDL4UED1	4 sq.mm Terminal Blocks with diode circuit - D1 configuration
CDL4UEDD5	4 sq.mm Terminal Blocks with diode circuit - DD5 configuration
CDL4UEL2	4 sq.mm Double Level Terminal Blocks with LED indication - L2 Configuration
CDL4UEL2	4 sq.mm Double Level Terminal Blocks with LED indication - L2 Configuration
CDL4UEL2	4 sq.mm Double Level Terminal Blocks with LED indication - LD2 Configuration
CDL4UER2	4 sq.mm Terminal Blocks with resistor circuit - R2 configuration
CDL4UESD	4 sq.mm Surge Suppression Terminal Blocks - with surge suppression diode.
CDL4U(E)3LA	4 sq.mm Surge Suppression Terminal Blocks
CDL4UEDD1	4 sq.mm Terminal Blocks with diode circuit - DD1 configuration
CDL4UEDD4	4 sq.mm Terminal Blocks with diode circuit - DD4 configuration
CDL4UEL1-24V	4 sq.mm Double Level Terminal Blocks with LED indication -LD1 Configuration

EPCDL4U



connectwell
THE RIGHT CONNECTION

SUITABLE FOR

CDL4UELD4	4 sq.mm Double Level Terminal Blocks with LED indication - LD4 Configuration
CDL4UELD5	4 sq.mm Double Level Terminal Blocks with LED indication - LD5 Configuration
CDL4UEN1	4 sq.mm Terminal Blocks with Neon Lamp indicator.