



End Plate

End Plates are used to cover the live parts of the last Terminal Block

PRODUCT SPECIFICATION

Height	41.8 mm
Length	72.7 mm
Width (Thickness)	1.5 mm

ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
EPCXDL2.5	End Plate in Grey Colour	50

SUITABLE FOR

CPDL2.5(E)DD4	2.5 sq.mm Terminal Blocks in push-in connection with diode circuit - DD4 configuration
CPDL2.5(E)LD1	2.5 sq.mm Double Level Terminal Blocks with LED indication for LD1 Configuration
CPDL2.5(E)TS1	2.5 sq.mm Double Level Terminal Blocks with Temperature Sensor indication - TS1 Configuration
CPDL2.5(I.S)	2.5 sq.mm Multiple Connection Internally Shorted Terminal Blocks with 4 connection points.
CXDL2.5(E)D1	2.5 sq.mm Terminal Blocks with diode circuit - D1 configuration
CXDL2.5(E)DD2	2.5 sq.mm Terminal Blocks with diode circuit - DD2 configuration
CXDL2.5(E)DD3	2.5 sq.mm Terminal Blocks with diode circuit - DD3 configuration
CXDL2.5(E)LD2	2.5 sq.mm Double Level Terminal Blocks with LED indication -LD2 Configuration
CXDL2.5(E)TS1	2.5 sq.mm Double Level Terminal Blocks with Temperature Sensor indication - TS1 Configuration
CXDLG2.5(I.S)	2.5 sq.mm Multiple Connection Earthing Terminal Blocks with 4 connection points.
CPDL2.5(E)D1	2.5 sq.mm Terminal Blocks with diode circuit - D1 configuration
CPDL2.5(E)D2	2.5 sq.mm Terminal Blocks with diode circuit - D2 configuration
CPDL2.5(E)DD5	2.5 sq.mm Terminal Blocks in push-in connection with diode circuit - DD5 configuration
CPDLG2.5	2.5 sq.mm Double Level Earthing Terminal Blocks.
CXDL2.5	2.5 sq.mm Double Level Spring Clamp Terminal Blocks
CXDL2.5(E)DD1	2.5 sq.mm Terminal Blocks with diode circuit - DD1 configuration
CXDL2.5(E)DD4	2.5 sq.mm Terminal Blocks with diode circuit - DD4 configuration
CXDL2.5(E)LD1	2.5 sq.mm Double Level Terminal Blocks with LED indication -LD1 Configuration
CPDL2.5(E)DD1	2.5 sq.mm Terminal Blocks in Pushin connection with diode circuit - DD1 configuration
CPDLG2.5(I.S)	2.5 sq.mm Multiple Connection Earthing Terminal Blocks with 4 connection points.
CXDL2.5(E)D2	2.5 sq.mm Terminal Blocks with diode circuit - D2 configuration
CXDL2.5(I.S)	2.5 sq.mm Multiple Connection Internally shorted Terminal Blocks with 4 connection points.
CPDL2.5	2.5 sq.mm Double Level Push in Terminal Blocks

EPCXDL2.5



connectwell
THE RIGHT CONNECTION

SUITABLE FOR

CPDL2.5(E)DD2	2.5 sq.mm Terminal Blocks in pushin connection with diode circuit - DD2 configuration
CPDL2.5(E)DD3	2.5 sq.mm Terminal Blocks in Push in with diode circuit - DD3 configuration
CPDL2.5(E)DD6	2.5 sq.mm Terminal Blocks in push-in connection with diode circuit - DD6 configuration
CXDL2.5(E)D3	2.5 sq.mm Terminal Blocks with diode circuit - D3 configuration
CXDLG2.5	2.5 sq.mm Double Level Earthing Terminal Blocks.