




















MULTIPLE CONNECTION TERMINAL BLOCKS

These blocks are used to connect multiple wires in a single Terminal Block, thereby eliminating reliability problems encountered when connecting multiple wires in a single clamp.

The terminals marked with  can be used in potentially explosive atmosphere. For detailed information refer page 119.



Terminal Block Pitch	6 mm		
Height x Width	51.5 x 65 mm		
Connection Possibility	Stranded Wire	0.5 to 4 sq.mm	
	Solid Wire	0.5 to 6 sq.mm	
Stripping Length	9 mm		
Insulation Material / Comparative Tracking Index	Polyamide 66 / I		
Type of Connection	 4 screw clamps and 2 tapped holes for cross connection		
Approvals			
Rated Connecting Capacity	22-10 AWG	0.5-4 sq.mm	22-10 AWG
Voltage Rating	600 V	630 V	600 V
Rated Impulse Voltage/Pollution Degree		6 KV / 3	
Current Rating	35 A	32 A	35 A
Torque	7 lb-in	0.5 Nm	7 lb-in
Other Approvals			

	Type Cat. No.	Std. Packing in Pcs.
Terminal Block	CMC2-2	50
End Plate 	EPCMC2-2	50
Separator Plate 		
Mounting Rail 	CA501 CA701 CA701-15	50 m 50 m 50 m
End Clamp 	CA702 CA802	50 50
Pre Assembled Shorting Links 	2 way CA722/2 3 way CA722/3 4 way CA722/4 10 way CA722/10 100 way CA722/100	100 100 100 10 10
Insulated Pre Assembled Shorting Link 	2 way CA742/2 3 way CA742/3 4 way CA742/4 10 way CA742/10 100 way CA742/100	100 100 100 10 10
Permanent Shorting Links 	2 way CA703/1 3 way CA704/1 4 way CA705/1 10 way CA732/10 10 way (Breakable) CA732/10-A 100 way CA732/100	100 100 100 100 100 10
Short Sleeve & Screw for Quick Permanent Shorting 	CA707/S/Q/01	100
Insulated Comb Type Shorting Link* 	2 way CA713/2 3 way CA713/3 4 way CA713/4 10 way CA713/10	100 100 100 20
Test Socket 	CA707/TS/01	100
Marking Tags (K Type) 	CA509/K6 CA509/K6F	100 10

* Comb links can be used only in the upper level clamping unit of the Terminal Block.