



STANDARD FEED THROUGH TERMINAL BLOCKS

These Feed Through Terminal Blocks are the most versatile terminals for Control, Automation, Instrumentation and Power Distribution applications.






















CTS25UN and CTS35UN are newer versions of the CTS25U and CTS35U terminals. These new Terminal Blocks are completely closed and do not require a separate end plate.

The terminals marked with  can be used in potentially explosive atmosphere. For detailed information refer page 119.



Terminal Block Pitch	12 mm		
Height x Width	56 x 49 mm		
Connection Possibility	Stranded Wire	6 to 25 sq.mm	
	Solid Wire	6 to 35 sq.mm	
Stripping Length	18 mm		
Insulation Material / Comparative Tracking Index	Polyamide 66 / I		
Type of Connection	 2 screw clamps and 1 tapped hole for cross connection		
Approvals			
Rated Connecting Capacity	12-2 AWG	6-25 sq.mm	12-2 AWG
Voltage Rating	600 V	800 V	600 V
Rated Impulse Voltage/Pollution Degree		8 KV / 3	
Current Rating	115 A	101 A	115 A
Torque	14 lb-in	2.0 Nm	14 lb-in

Other Approvals

	Type Cat. No.	Std. Packing in Pcs.
Terminal Block	CTS25UN	50
End Plate 		
Partition Plate 	PP25UN	50
Separator Plate 		
Mounting Rail	CA501 CA701 CA701-15	50 m 50 m 50 m
End Clamp 	CA702 CA802	50 50
Pre Assembled Shorting Links	2 way  3 way  4 way  10 way  100 way 	CA725/2 50 CA725/3 20 CA725/4 20 CA725/10 10
Insulated Pre Assembled Shorting Link	2 way  3 way  4 way  10 way  100 way 	CA745/2 50 CA745/3 20 CA745/4 20 CA745/10 10
Permanent Shorting Links	2 way  3 way  4 way  10 way 	CA703/4 100 CA704/4 100 CA705/4 100 CA735/10 100
Short Sleeve & Screw for Quick Permanent Shorting 	CA707/S/Q/2	100
Test Socket 	CA707/TS/06	100
Marking Tags (K Type) Continuous Tag 	CA509/K12 CA509/K6F	100 10