
























STANDARD FEED THROUGH TERMINAL BLOCKS

These Feed Through Terminal Blocks are the most versatile terminals for Control, Automation, Instrumentation and Power Distribution applications. A specially designed flexible foot enables easy mounting and dismounting from the mounting rail with the help of a screw driver. These Terminal Blocks have marker holding recesses to accept marking tags for circuit identification. Cross connection can be achieved with the aid of shorting links / sleeves & screws.

The terminals marked with  can be used in potentially explosive atmosphere. For detailed information refer page 119.

CTS4UN



Terminal Block Pitch	6 mm		
Height x Width	45 x 43 mm		
Connection Possibility	Stranded Wire	0.5 to 4 sq.mm	
	Solid Wire	0.5 to 6 sq.mm	
Stripping Length	9 mm		
Insulation Material / Comparative Tracking Index	Polyamide 66 / I		
Type of Connection	 2 screw clamps and 1 tapped hole for cross connection		
Approvals			
Rated Connecting Capacity	22-10 AWG	0.5-4 sq.mm	22-10 AWG
Voltage Rating	600 V	800 V	600V
Rated Impulse Voltage/Pollution Degree		8 KV / 3	
Current Rating	40 A *	32 A	40 A *
Torque	7 lb-in	0.5 Nm	7 lb-in
Other Approvals			 AEx eII Ex eII
	Type	Std. Packing	
	Cat. No.	in Pcs.	
Terminal Block	CTS4UN	100	
End Plate 	EP2.5/4UN	50	
Partition Plate 	PP2.5/4UN	50	
Separator Plate 	SP2.5/4UN	100	
Mounting Rail	CA501	50 m	
	CA701	50 m	
	CA701-15	50 m	
End Clamp	CA702	50	
	CA802	50	
Pre Assembled Shorting Links	2 way 	CA722/2	100
	3 way	CA722/3	100
	4 way 	CA722/4	100
	10 way	CA722/10	10
	100 way	CA722/100	10
Insulated Pre Assembled Shorting Link	2 way 	CA742/2	100
	3 way	CA742/3	100
	4 way 	CA742/4	100
	10 way	CA742/10	10
	100 way	CA742/100	10
Permanent Shorting Links	2 way 	CA703/1	100
	3 way	CA704/1	100
	4 way	CA705/1	100
	10 way	CA732/10	100
	10 way (Breakable)	CA732/10-A	100
	100 way	CA732/100	10
Short Sleeve & Screw for Quick Permanent Shorting		CA707/S/Q/01	100
Removable Shorting Links		CA706/1	100
Long Sleeve & Screw for Temporary Shorting		CA707/L/Q/01	100
Insulated Comb Type Shorting Link	2 way 	CA713/2	100
	3 way	CA713/3	100
	4 way	CA713/4	100
	10 way	CA713/10	20
Test Socket		CA707/TS/01	100
Marking Tags (K Type) Continuous Tag		CA509/K6	100
		CA509/K6F	10

* 40 Amp with two 12 AWG wires
35 Amp with one 10 AWG wire