



















STANDARD FEED THROUGH TERMINAL BLOCKS

These Feed Through Terminal Blocks are the most versatile terminals for Control, Automation, Instrumentation and Power Distribution applications.

CTS25UN and CTS35UN are newer versions of the CTS25U and CTS35U terminals. These new Terminal Blocks are completely closed and do not require a separate end plate.

The terminals marked with  can be used in potentially explosive atmosphere. For detailed information refer page 119.



Terminal Block Pitch	20.5 mm		
Height x Width	75.5 x 71 mm		
Connection Possibility	Stranded Wire	16 to 50 sq.mm	
	Solid Wire	16 to 70 sq.mm	
Stripping Length	22 mm		
Insulation Material / Comparative Tracking Index	Polyamide 66 / I		
Type of Connection		2 screw clamp connection	
Approvals			
Rated Connecting Capacity	6 - 2/0 AWG	16-50 sq.mm	6 - 2/0 AWG
Voltage Rating	600 V	1000 V	600 V
Rated Impulse Voltage/Pollution Degree		8 KV / 3	
Current Rating	150 A	150 A	150 A
Torque	60 lb-in	6.8 Nm	60 lb-in
Other Approvals			
	Type Cat. No.	Std. Packing in Pcs.	
Terminal Block	CTS50U	20	
End Plate			
Partition Plate			
Separator Plate			
Mounting Rail		CA501 CA701 CA701-15	50 m 50 m 50 m
End Clamp		CA202 CA102	50 50
Pre Assembled Shorting Links	2 way 3 way 4 way 10 way 100 way 		
Insulated Pre Assembled Shorting Link	2 way 3 way 4 way 10 way 100 way 		
Permanent Shorting Links	2 way 3 way 4 way 10 way 		
Short Sleeve & Screw for Quick Permanent Shorting			
Test Socket			
Marking Tags (K Type) Continuous Tag		CA509/K20	100