





















# STANDARD FEED THROUGH TERMINAL BLOCKS

These Feed Through Terminal Blocks are the most versatile terminals for Control, Automation, Instrumentation and Power Distribution applications. A specially designed flexible foot enables easy mounting and dismounting from the mounting rail with the help of a screw driver. These Terminal Blocks have marker holding recesses to accept marking tags for circuit identification. Cross connection can be achieved with the aid of shorting links / sleeves & screws.

The terminals marked with  can be used in potentially explosive atmosphere. For detailed information refer page 119.



Terminal Block Pitch		8 mm		
Height x Width		47 x 43 mm		
Connection Possibility	Stranded Wire	1.5 to 6 sq.mm		
	Solid Wire	1.5 to 10 sq.mm		
Stripping Length		12 mm		
Insulation Material / Comparative Tracking Index		Polyamide 66 / I		
Type of Connection		 2 screw clamps and 1 tapped hole for cross connection		
Approvals				
Rated Connecting Capacity		22-8 AWG	1.5-6 sq.mm	22-8 AWG
Voltage Rating		600 V	800 V	600 V
Rated Impulse Voltage/Pollution Degree			8 KV / 3	
Current Rating		50 A	41 A	50 A
Torque		9 lb-in	0.8 Nm	14 lb-in
Other Approvals				 AEx eII Ex eII
		<b>Type Cat. No.</b>	<b>Std. Packing in Pcs.</b>	
Terminal Block		CTS6U	100	
End Plate 		EP6/10U	50	
Partition Plate 		PP6/10U	50	
Separator Plate 		SP6/10U	100	
Mounting Rail		CA501	50 m	
		CA701	50 m	
		CA701-15	50 m	
End Clamp		CA702	50	
		CA802	50	
Pre Assembled Shorting Links		2 way 	CA723/2	100
		3 way	CA723/3	50
		4 way	CA723/4	50
		10 way	CA723/10	10
		100 way		
Insulated Pre Assembled Shorting Link		2 way 	CA743/2	100
		3 way	CA743/3	50
		4 way	CA743/4	50
		10 way	CA743/10	10
		100 way		
Permanent Shorting Links		2 way 	CA703/2	100
		3 way	CA704/2	100
		4 way	CA705/2	100
		10 way	CA733/10	100
		10 way (Breakable)		
		100 way		
Short Sleeve & Screw for Quick Permanent Shorting			CA707/S/Q/1	100
Removable Shorting Links			CA706/2	100
Long Sleeve & Screw for Temporary Shorting			CA707/L/Q/1	100
Insulated Comb Type Shorting Link		2 way 	CA710/2	100
		3 way	CA710/3	50
		4 way	CA710/4	50
		10 way	CA710/10	20
Test Socket			CA707/TS/05	100
Marking Tags (K Type) Continuous Tag			CA509/K8	100
			CA509/K6F	10

\* 40 Amp with two 12 AWG wires  
35 Amp with one 10 AWG wire