



















STANDARD FEED THROUGH TERMINAL BLOCKS

These Feed Through Terminal Blocks are the most versatile terminals for Control, Automation, Instrumentation and Power Distribution applications.

CTS25UN and CTS35UN are newer versions of the CTS25U and CTS35U terminals. These new Terminal Blocks are completely closed and do not require a separate end plate.

The terminals marked with  can be used in potentially explosive atmosphere. For detailed information refer page 119.



| | | | |
|---|---|--|---|
| Terminal Block Pitch | 25 mm | | |
| Height x Width | 90 x 83 mm | | |
| Connection Possibility | Stranded Wire | 25 to 95 sq.mm | |
| | Solid Wire | 25 to 120 sq.mm | |
| Stripping Length | 24 mm | | |
| Insulation Material / Comparative Tracking Index | Polyamide 66 / I | | |
| Type of Connection |  | 2 Allen screw clamp connection | |
| Approvals |  |  |  |
| Rated Connecting Capacity | 2 - 4/0 AWG | 25-95 sq.mm | 2 - 4/0 AWG |
| Voltage Rating | 600 V | 1000 V | 600 V |
| Rated Impulse Voltage/Pollution Degree | | 8 KV / 3 | |
| Current Rating | 230 A | 232 A | 230 A |
| Torque | 160 lb-in | 10.0 Nm | 160 lb-in |
| Other Approvals |  |  | |
| | Type Cat. No. | Std. Packing in Pcs. | |
| Terminal Block | CTS95U | 10 | |
| End Plate |  | | |
| Partition Plate |  | | |
| Separator Plate |  | | |
| Mounting Rail |  | CA501 CA701 CA701-15 | 50 m 50 m 50 m |
| End Clamp |  | CA202 CA102 | 50 50 |
| Pre Assembled Shorting Links |  | | |
| | 2 way 3 way 4 way 10 way 100 way | | |
| Insulated Pre Assembled Shorting Link |  | | |
| | 2 way 3 way 4 way 10 way 100 way | | |
| Permanent Shorting Links |  | | |
| | 2 way 3 way 4 way 10 way | | |
| Short Sleeve & Screw for Quick Permanent Shorting |  | | |
| Test Socket |  | | |
| Marking Tags (K Type) Continuous Tag |  | CA509/K25 | 100 |