


# DOUBLE LEVEL TERMINAL BLOCKS



Functionally similar to the CDL4U, in the ODL4U Terminal Block, the top level is offset from the bottom level by half the thickness of the Terminal Block. This creates better access for the bottom level screws while the wires are connected. It is recommended to use End Plates at both ends of the assembled ODL4U sets for flat alignment to enable the effective use of End Clamp.

ODL4UA Terminal Block is modified version of ODL4U, with 'Modular' feature, where the Terminal Blocks can be stacked to form multi-pole assembly.

These blocks are ideal for use in applications requiring high density wiring. Interconnection/shorting is possible at both levels.

The CDLG2.5 is a double level Terminal Block with an additional connection point for earthing (Grounding) cables. This separate connection point is appropriately identified by the green-yellow imprint on its top.

In the CDL4U(I.S) and CDL4UN(I.S) Terminal Blocks, both levels are internally shorted. These blocks are useful for distribution application with the aid of shorting links at the lower level.

The terminals marked with can be used in potentially explosive atmosphere. For detailed information refer page 119.

Terminal Block Pitch	6 mm		
Height x Width	63 x 68 mm		
Connection Possibility	Stranded Wire	0.5 to 4 sq.mm	
	Solid Wire	0.5 to 6 sq.mm	
Stripping Length	9 mm		
Insulation Material / Comparative Tracking Index	Polyamide 66 / I		
Type of Connection			
Approvals			
Rated Connecting Capacity	22-10 AWG	0.5-4 sq.mm	22-10 AWG
Voltage Rating	600 V	630 V	600 V
Rated Impulse Voltage/Pollution Degree		6 KV / 3	
Current Rating	35 A	32 A	35 A
Torque	7 lb-in	0.5 Nm	7 lb-in

Other Approvals		Type Cat. No.	Std. Packing in Pcs.
Terminal Station		ODL4UA	50
End Plate	Front Side	EPODL4U	50
	Back Side	EP1ODL4U	50
Separator Plate			
Mounting Rail		CA501	50 m
		CA701	50 m
		CA701-15	50 m
End Clamp		CA702	50
		CA802	50
		CA202	50
Pre Assembled Shorting Links	2 way	CA727/2	100
	3 way	CA727/3	100
	4 way	CA727/4	100
	10 way	CA727/10	10
	Insulated Pre Assembled Shorting Link	2 way	CA747/2
	3 way	CA747/3	100
	4 way	CA747/4	100
	10 way	CA747/10	10
Permanent Shorting Links	2 way	CA703/1	100
	3 way	CA704/1	100
	4 way	CA705/1	100
	10 way	CA732/10	100
	10 way(Breakable)	CA732/10-A	100
	100 way	CA732/100	10
	Short Sleeve & Screw for Quick Permanent Shorting		CA607/S/Q
Insulated Comb Type Shorting Link	2 way	CA714/2	100
	3 way	CA714/3	100
	4 way	CA714/4	100
	10 way	CA714/10	20
Test Socket		CA707/TS/01	100
Marking Tags (K Type) Continuous Tag		CA509/K6	100
		CA509/K6F	10