

CA512/13-2



Removable Shorting Links

These links have a possibility of quick insertion and removal. The entire nut assembly of the Terminal Block need not be removed for the insertion or removal of these links. They are available in standard 2, 3 or 4 pole configurations. They are also available in an insulated version which provides shock protection when installed on Terminal Blocks.

PRODUCT SPECIFICATION

Rated Current	41 A
Torque	1.2 Nm

ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
CA512/13-2	Removable Shorting link available in 2 Pole	100
CA512/13-3	Removable Shorting link available in 3 Pole	50
CA512/13-4	Removable Shorting link available in 4 Pole	50

SUITABLE FOR

STH4DTSH	6 sq. mm M4 Stud Disconnect & Test shorted Terminal Block - with captive nuts.
STH4DT	Stud Type Terminal Block
STH4DTFT	Stud Type Terminal Block
STH4DTNS	Stud Type Terminal Block
STH4DTTP	6 sq. mm M4 Stud Disconnect & Test Terminal Block - with captive nuts.
CBDT4UNS	6 sqmm Stud type Disconnect Terminal Blocks
STH4	6 sq. mm Stud Type Terminal Block - with captive nuts.
STH4DT/SW	6 sq.mm Stud/Nut Type Disconnect and Test Terminal Block with 1 Threaded and 1 Non Threaded Test Socket Terminal Block in Grey Colour