

CA512/1-2



connectwell
THE RIGHT CONNECTION

Removable Shorting Links

These links have a possibility of quick insertion and removal. The entire nut assembly of the Terminal Block need not be removed for the insertion or removal of these links. They are available in standard 2, 3 or 4 pole configurations. They are also available in an insulated version which provides shock protection when installed on Terminal Blocks.

PRODUCT SPECIFICATION

Torque	76 Nm
Width (Thickness)	1.2 mm

ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
CA512/1-2	Removable Shorting Link available in 2 Pole	100
CA512/1-3	Removable Shorting Link available in 3 Pole	50
CA512/1-4	Removable Shorting Link available in 4 Pole	50

SUITABLE FOR

CSTSB4U	Screwdriver operated M4 sized Stud Type Terminal Blocks, with Universal Mounting Possibility.
CSTSN5U	Nut driver operated M5 sized Stud Type Terminal Blocks, with Universal Mounting Possibility.
CSN4U	Nut driver operated M4 sized Stud Type Terminal Blocks, with Universal Mounting Possibility.
CSTSN4	M4 sized Stud Type Terminal Blocks, suitable for operation with nut driver.
CSTSN4U	Nut driver operated M4 sized Stud Type Terminal Blocks, with Universal Mounting Possibility.
CSTSN5	M5 sized Stud Type Terminal Blocks, suitable for operation with nut driver.
CSN5U	Nut driver operated M5 sized Stud Type Terminal Blocks, with Universal Mounting Possibility.
CSTSB5U	Screwdriver operated M5 sized Stud Type Terminal Blocks, with Universal Mounting Possibility.