

CA512/8-2



**connectwell**  
THE RIGHT CONNECTION

### Ring Type Shorting Link

These links have a possibility of quick insertion and removal. The entire nut assembly of the Terminal Block need not be removed for the insertion or removal of these links. They are available in standard 2, 3 or 4 pole configurations. They are also available in an insulated version which provides shock protection when installed on Terminal Blocks.

#### PRODUCT SPECIFICATION

Rated Current	125 A
Torque	1.2 Nm

#### ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
CA512/8-2	Ring Type Shorting Link available in 2 Pole	100
CA512/8-3	Ring Type Shorting Link available in 3 Pole	50
CA512/8-4	Ring Type Shorting Link available in 4 Pole	50

#### SUITABLE FOR

CSTSN6USH	Nut driver operated M6 sized Stud Type Hinge Terminal Blocks, with Universal Mounting Possibility.
CSTSN6	M6 sized Stud Type Terminal Blocks, suitable for operation with nut driver.
CSTSN6U	Nut driver operated M6 sized Stud Type Terminal Blocks, with Universal Mounting Possibility.
CSTSN6UE	Nut driver operated M6 sized Stud Type Terminal Blocks, with Universal Mounting Possibility.