


CPST1.5/4



1.5 sqmm sensor & Actuator Terminal Block

Sensor and actuator Terminal Blocks are ideal for wiring modern machine control systems.

TECHNICAL DATA

Rated Voltage	250 V
Rated Current	13.5 A

CONNECTION DATA

Conductor Cross Section Stranded min.	0.2 mm ²
Conductor Cross Section Stranded max.	1.5 mm ²


DIMENSIONS

Height with DIN 35 x 15 mm rail	55.55 mm
Height with DIN 35 x 7.5 mm rail	48.1 mm
Length	96.5 mm
Width (Thickness)	3.5 mm

ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
CPST1.5/4L6-60V	1.5 sqmm sensor and actuator Push in Terminal Block	50
CPST1.5/4	1.5 sqmm sensor and actuator Push in Terminal Block	50
CPST1.5/4L110-240V	1.5 sqmm sensor and actuator Push in Terminal Block	50

ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	MC3.5	MARKER CARD 3.5MM PITCH WITH 120 TAGS	10

APPROVALS




NOTES

The Rated current is with the use of copper (Cu) conductor/Wire

RATINGS AS PER STANDARDS

STANDARDS	UL 1059	IEC/EN60947-7-1
Approvals	UL	CE
Conductor Cross Section Stranded min.	24 AWG	0.2 mm ²
Conductor Cross Section Stranded max.	14 AWG	1.5 mm ²
Rated Voltage	150 V	250 V

CPST1.5/4



connectwell
THE RIGHT CONNECTION

RATINGS AS PER STANDARDS

Rated Current

15 A

13.5 A